Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-2.   (Canceled)

3.   (Currently Amended):   An image processor comprising:

voltage band determination means for determining a voltage band for an image to be displayed which are generated by an image sensor outputting a compressed image (compressive image sensor) in response to the light received by said compressive image sensor; and

image conversion means for converting said voltage band by expanding said band,

The image processor according to claim 1, wherein said image conversion means further comprises:

subtraction means for subtracting the lower limit of said voltage band from said voltage band so as to match the lower limit of said subtracted band with a prescribed post-conversion minimum Lmin; and

multiplication means for converting said subtracted band so as to match the upper limit of the converted band with a prescribed post-conversion maximum Lmax.

4.   (Currently Amended):   An image processor comprising:

voltage band determination means for determining a voltage band for an image to be displayed which are generated by an image sensor outputting a

Appl. No. 09/943,218
Amdt. Dated October 27, 2004
Reply to Office Action of July 1, 2004

Attorney Docket No. 81876.0024
Customer No.: 26021

compressed image (compressive image sensor) in response to the light received by said compressive image sensor; and

image conversion means for converting said voltage band by expanding said band,

~~The image processor according to claim 1,~~ wherein said image conversion means further comprises:

multiplication means for matching the upper limit of said voltage width with a given post-conversion maximum Lmax; and

operational means for matching the lower limit of the multiplied voltage width with a given post-conversion minimum Lmin.

5.   (Original) An image processor comprising:

first conversion means for obtaining first conversion data D' for the entire pixel data D lying within a significant voltage band Dmin - Dmax by

(i)   constructing a ratio R of the sum of the assessment pixel data belonging to an assessment area that precedes currently processing pixel data D to the sum of said assessment pixel data summed on the assumption that all of said assessment pixel data have maximum possible values,

(ii)   multiplying each of the pixel data D by said ratio R and a first predetermined coefficient A, and

(iii)   replacing by a prescribed post-conversion maximum Lmax those pixel data that exceed said maximum Lmax upon multiplication of said ratio R and said coefficient A; and

second conversion means for obtaining second conversion data D" by

\\\LA - 81876/0024 - 209416 v1

Appl. No. 09/943,218
Amdt. Dated October 27, 2004
Reply to Office Action of July 1, 2004

Attorney Docket No. 81876.0024
Customer No.: 26021

(iv)   subtracting each of said pixel data D' from post-conversion maximum Lmax,

(v)   multiplying each of the subtracted data of (i) by a second predetermined coefficient B,

(vi)   replacing by said post-conversion maximum Lmax those pixel data that exceed said post-conversion maximum Lmax upon multiplication of said coefficient B, and

(vii)   subtracting again from said post-conversion maximum Lmax each of the data that result from the foregoing steps (iv) -(vi).

6.   (Original) The image processor according to claim 5, wherein said first conversion means has a feedback loop to decrease said first coefficient A by a predetermined magnitude when the number of the pixel data replaced by said post-conversion maximum Lmax is greater than a predetermined number N1, but increment said coefficient A by a predetermined magnitude when said replaced number of pixel data is less than a predetermined number N2.

7.   (Original) The image processor according to claim 5, wherein said second conversion means has a feedback loop to decrease said second coefficient B by a predetermined magnitude when the number of pixel data replaced by said post-conversion maximum Lmax is greater than a predetermined number N3, but increment said coefficient B by a predetermined magnitude when said replaced number of pixel data is less than a predetermined number N4.

Appl. No. 09/943,218
Amdt. Dated October 27, 2004
Reply to Office Action of July 1, 2004

Attorney Docket No. 81876.0024
Customer No.: 26021

8.   (Original) The image processor according to claim 5, wherein

said second Lmax is replaced by Lmax' = Lmax − Lmin in said first and said second conversion means when said minimum Lmin is a positive/negative number (other than zero); and

said second conversion means is adapted to output the sum of said second converted pixel data D" and Lmin.

9.   (Original) The image processor according to claim 8, adapted to subtract said post-conversion minimum Lmin from all of the pixel data D prior to said first conversion.

10.   (Original) An image processor, comprising:

first conversion means for converting all the pixel data D lying in a voltage band in a range Dmin − Dmax to obtain first converted pixel data D' by

(i)   multiplying said pixel data D by a third coefficient C1 having a predetermined initial value,

(ii)   replacing those converted pixel data that exceed a prescribed post-conversion maximum Lmax by Lmax; and

second conversion means for obtaining second conversion data D" by

(iii)   subtracting each of said first converted pixel data D' from said post-conversion maximum Lmax,

(iv)   multiplying the result of said subtraction in (iii) by a fourth multiplication coefficient C2,

(v)   replacing by said post-conversion maximum Lmax those pixel data that exceed Lmax upon multiplication of C2 in (iv), and

(vi)   again subtracting from Lmax each of the resultant pixel data obtained in steps (iii) − (v).

Appl. No. 09/943,218
Amdt. Dated October 27, 2004
Reply to Office Action of July 1, 2004

Attorney Docket No. 81876.0024
Customer No.: 26021

11.   (Original) The image processor according to claim 10, wherein said first conversion means has a feedback loop to decrease said third coefficient C1 by a predetermined magnitude when the number of pixel data replaced by said post-conversion maximum Lmax is greater than a predetermined number N1, but increment said coefficient C1 by a predetermined magnitude when said replaced number of pixel data is less than a predetermined number N2.

12.   (Original) The image processor according to claim 10, wherein said second conversion means has a feedback loop to decrease said fourth coefficient C2 by a predetermined magnitude when the number of pixel data replaced by said post-conversion maximum Lmax is greater than a predetermined number N3, but increment said coefficient C2 by a predetermined magnitude when said replaced number of pixel data is less than a predetermined number N4.

13.   (Original) The image processor according to claim 10, wherein

said first and said second conversion means are adapted to replace said post-conversion maximum Lmax by a modified post-conversion maximum defined by Lmax' = Lmax − Lmin when said post-conversion minimum Lmin is not zero, and wherein

said second conversion means is further adapted to add said post-conversion minimum Lmin to said second converted pixel data D".

14.   (Original) The image processor according to claim 13, adapted to subtract said post-conversion minimum Lmin from all of the pixel data D prior to said first conversion.